

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY OF
A PORTION OF THE
NORTH BOUNDARY (UINTAH SPECIAL BASE LINE),
A PORTION OF THE
SUBDIVISIONAL LINES
AND THE
SUBDIVISION OF SECTIONS 3, 4, 5, 9, AND 10,
IN
TOWNSHIP 1 SOUTH, RANGE 3 WEST
OF THE UINTAH SPECIAL MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Jerry L. Thomas
Cadastral Surveyor

Under special instructions dated *March 24 1993*, approved *April 27, 1993*, which provided for the surveys included under Group Number *800*, and assignment instructions dated *May 19, 1993*.

Survey commenced *June 30, 1993*

Survey completed *May 29, 1997*

INDEX DIAGRAM

Township 1 South, Range 3 West

8	7	5	3	2	
	24	22	20		
6 23	5 21	4 19	3 15	2	1
	22	20	18		
7	8	9 17	10 14	11	12
			16		
18	17	16	15 13	14	13
19	20	21	22 12	23	24
30	29	28	27 12	26	25
31	32	33	34 10	35	36

The Survey of the Subdivision of Section 3.....Page 24

The Survey of the Subdivision of Section 4.....Page 25

The Survey of the Subdivision of Section 5.....Page 27

The Survey of the Subdivision of Section 9.....Page 29

The Survey of the Subdivision of Section 10.....Page 31

TOWNSHIP 1 SOUTH, RANGE 3 WEST,
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the north boundary (Uintah Special Base Line); a portion of the subdivisional lines; and the subdivision of sections 3, 4, 5, 9, and 10, T. 1 S., R. 3 W., Uintah Special Meridian, Utah.

History of Surveys

Surveyed by

Retr. or Resurveyed by

NORTH BOUNDARY

All	H.D. Heist	1903
-----	------------	------

SOUTH BOUNDARY

All	D.G. Major	1882
All		G.C. Swan and F.C. Ferron 1904

EAST BOUNDARY

All	G.C. Swan and F.C. Ferron	1904
-----	------------------------------	------

WEST BOUNDARY

All	D.G. Major	1882
Portion		H.D. Heist 1903
Portion		G.C. Swan and F.C. Ferron 1904

SUBDIVISION

All	G.C. Swan and F.C. Ferron	1904
-----	------------------------------	------

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 800, Utah, dated March 24, 1993.

The direction of the lines of this survey refer to the true meridian, determined by hour angle observations of the sun and Polaris and carried forward by means of sustained angulation. The measurements of these lines were made with an electronic distance measuring device. Horizontal distances only are entered in the field notes.

TOWNSHIP 1 SOUTH, RANGE 3 WEST,
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

Note: The north boundary of section 6, was resurveyed by Frank Profazer in 1995, and is now considered part of this survey.

The geographic position of the southwest corner of section 35, as determined by GPS method using U.S. Geological Survey triangulation station, "LA MINK", is as follows:

Latitude: 40° 20' 41.670" N. Longitude: 110° 11' 58.051" W.
N.A.D. 1983

This corner will also function as a B.L.M. control station.

The mean magnetic declination as determined from numerous readings throughout the survey is: 13 1/2 East.

Dependent Resurvey of a Portion of the South Boundary,
(Uintah Special Base Line), T. 1 N., R. 3 W.,
Uintah Special Meridian, Utah

(Reestablishment of the Survey Executed by
H.D. Heist in 1903)

Beginning from the standard 1/4 section corner of section 35 only, T. 1 N., R. 3 W., on the Uintah Special Base Line, monumented with a trachyte stone, 16x10x8 inches, firmly set, projecting 8 inches above ground, plainly marked SC 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

SC
T1N R3W
1/4 S35
1993

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
(UINTAH SPECIAL BASE LINE), T. 1 N., R. 3 W.,
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

N. 89° 41.5' W., on the south boundary of section 35, T. 1 N., R. 3 W.

Over rolling land.

31.79

The closing corner of sections 2 and 3, T. 1 S., R. 3 W., on the Uintah Special Base Line, monumented with a sandstone, 12x10x6 inches, firmly set, projecting 8 inches above ground, plainly marked 2 notches on the E. and 4 notches on the W. edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, and in a collar of stone, with aluminum cap marked:

T1N	
<u>S35</u>	
S3	S2
C	C
T1S R3W	
1993	

Deposit the marked stone alongside the aluminum post.

Corner is located 2 links E of fence corner, with fences projecting E, W, and N.

40.195

The standard corner of sections 34 and 35, T. 1 N., R. 3 W., on the Uintah Special Base Line, monumented with a sandstone, 16x8x6 inches, firmly set, projecting 10 inches above ground, plainly marked 2 notches on the E and 4 notches on the W edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

SC	
T1N R3W	
<u>S34</u>	<u>S35</u>
1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

Corner is located in E-W fence line.

S. 89° 12' W., on the south boundary of section 34.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
(UINTAH SPECIAL BASE LINE), T. 1 N., R. 3 W.,
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS**11.00**

Dirt road, bears NW. and SE.

31.185

Point for the 1/4 section corner of section 3 only, T. 1 S., R. 3 W., on the Uintah Special Base Line, hereinafter described.

40.185

The standard 1/4 section corner of section 34 only, T. 1 N., R. 3 W., on the Uintah Special Base Line, monumented with a trachyte stone, 18x12x6 inches, firmly set, projecting 10 inches above ground, plainly marked SC 1/4 on the N face, from which the remaining original bearing tree

A cedar, 8 inches diameter, bears N. 32° 20' W., 12 links distance,
marked SC 1/4 S34 BT.

There is no remaining evidence of the other bearing tree.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

SC
T1N R3W
1/4 S34
1993

Deposit the marked stone alongside the aluminum post.

N. 89° 34.5' W., beginning new measurement.

30.59

The closing corner of sections 3 and 4, T. 1 S., R. 3 W., on the Uintah Special Base Line, monumented with a limestone, 15x8x4 inches, firmly set, projecting 6 inches above ground, plainly marked 3 notches on the E. and W. edges, and 6 notches on the S. edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, and in a collar of stone, with aluminum cap marked:

T1N
S34
S4 | S3
CC
T1S R3W
1993

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
(UINTAH SPECIAL BASE LINE), T. 1 N., R. 3 W.,
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Corner is located in E and W fence line.

38.50

Dirt road, bears NE. and SW.

40.045

The standard corner of sections 33 and 34, T. 1 N., R. 3 W., on the Uintah Special Base Line, monumented with a sandstone, 16x10x8 inches, firmly set, projecting 6 inches above ground, plainly marked SC on the N. face, and 3 notches on the E and W edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top, with aluminum cap marked:

SC
T1N R3W
S33 | S34
1993

Deposit the marked stone alongside the aluminum post.

S. 89° 49' W., on the south boundary of section 33.

Over rolling land.

30.92

Point for the 1/4 section corner of section 4 only, T. 1 S., R. 3 W., on the Uintah Special Base Line, hereinafter described.

40.17

The standard 1/4 section corner of section 33, T. 1 N., R. 3 W., on the Uintah Special Base Line, monumented with a trachyte stone, 16x12x8 inches, firmly set, projecting 10 inches above ground, plainly marked SC 1/4 on the N. face, from which the original bearing trees:

A cedar, 8 inches diameter, bears N. 18° E., 11 links distance,
marked SC 1/4 S BT.

A cedar, 12 inches diameter, bears N. 41 W., 54 links distance,
marked SC 1/4 S BT.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
(UINTAH SPECIAL BASE LINE), T. 1 N., R. 3 W.,
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

SC
T1N R3W
1/4 S33
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

S. 89° 56' W., beginning new measurement.

31.13

The closing corner of sections 4 and 5, T. 1 S., R. 3 W., on the Uintah Special Base Line, monumented with a cobblestone, 20x14x8 inches, firmly set, projecting 10 inches above ground, plainly marked CC on the S. face, 4 grooves on the E., and 2 grooves on the W. faces, from which the original bearing trees:

A cedar, 13 inches diameter, bears S. 89° W., 22 links distance,
marked T1S R3W S5 BT.

A pinon, 20 inches diameter, bears S. 50° E., 44 links distance,
marked T1S R3W S4 BT.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1N
S33
S5 S4
C C
T1S R3W
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone south of the corner.

40.08

The standard corner of sections 32 and 33, T. 1 N., R. 3 W., on the Uintah Special Base Line, monumented with a trachyte stone, 18x12x10 inches, firmly set, projecting 10 inches above ground, plainly marked SC on the N. face, 4 notches on the E., and 2 notches on the W. edges, from which the original bearing trees:

A cedar, 7 inches diameter, bears N. 42° E., 37 links distance,
marked T1N R3W S33 BT.

A cedar, 8 inches diameter, bears N. 25° W., 39 links distance,
marked T1N R3W S32 BT.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
(UINTAH SPECIAL BASE LINE), T. 1 N., R. 3 W.,
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

SC
T1N R3W
S32 | S33
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

S. 89° 45' W., on the south boundary of section 32.

Over rolling and broken land.

30.89 Point for the 1/4 section corner of section 5 only, T. 1 S., R. 3 W., on the Uintah Special Base Line, hereinafter described.

39.95 The standard 1/4 section corner of section 32, T. 1 N., R. 3 W., on the Uintah Special Base Line, monumented with a sandstone, 16x10x8 inches, firmly set, projecting 8 inches above ground, plainly marked SC on the N. face and 1/4 on the S. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

SC
T1N R3W
1/4 S32
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone south of the corner.

S. 89° 59' W., beginning new measurement.

30.77 The closing corner of sections 5 and 6, T. 1 S., R. 3 W., on the Uintah Special Base Line, monumented with a cobblestone, 13x10x5 inches, firmly set, projecting 8 inches above ground, plainly marked CC on S. face, 1 groove on W. face, and 5 grooves on the E. face, from which the original bearing trees:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
(UINTAH SPECIAL BASE LINE), T. 1 N., R. 3 W.,
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

A pinon, 14 inches diameter, bears S. 87° E., 32 links distance,
marked T1S R3W S5 BT.

A pinon, 10 inches diameter, bears S. 41° W., 44 links distance,
marked T1S R3W S6 BT.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the
ground, with aluminum cap marked:

T1N	
<u>S32</u>	
S6	S5
C	C
T1S R3W	
1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone south of the corner.

40.04

The standard corner of sections 31 and 32, on the Uintah Special Base Line,
monumented with a trachyte stone, 18x10x5 inches, firmly set, projecting 10 inches
above ground, plainly marked SC on the N. face, 1 notch on the W., and 5 notches
on the E. edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the
ground, with aluminum cap marked:

SC	
T1N R3W	
<u>S31</u>	<u>S32</u>
1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

S. 89° 57' W., on the south boundary of section 31.

Over rolling and broken land.

30.69

Point for the 1/4 section corner of section 6 only, T. 1 S., R. 3 W., on the Uintah
Special Base Line.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
(UINTAH SPECIAL BASE LINE), T. 1 N., R. 3 W.,
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

This corner point not monumented.

40.11

The standard 1/4 section corner of section 31, T. 1 N., R. 3 W., on the Uintah Special Base Line, monumented with a sandstone, 18x12x5 inches, firmly set, projecting 10 inches above ground, plainly marked SC on the N. face, and 1/4 on the S. face, from which the original bearing trees:

A cedar, 12 inches diameter, bears N. 80° W., 35 links distance,
marked SC 1/4 BT.

A pinon, 20 inches diameter, bears N. 56° E., 73 links distance,
marked SC 1/4 BT.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

SC
T1N R3W
1/4 S31
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

Corner is located in E and W fence line.

N. 89° 57' W., beginning new measurement.

40.36

The original closing corner point for Tps. 1 N. and 1 S., R. 3 W., determined from the remaining original bearing tree:

A pinon, 16 inches diameter, bears S. 19° E., 34 links distance,
marked T1S R3W S6 BT.

There is no remaining evidence of the other bearing tree.

This point falls in E and W fence line.

40.61

Intersect the east boundary of section 36, T. 1 N., R. 4 W.

Point for the closing corner of Tps. 1 N. and 1 S., R. 3 W.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, and in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
(UINTAH SPECIAL BASE LINE), T. 1 N., R. 3 W.,
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

T1N	
R4W	R3W
S36	S31 C
	S6 C
T1S	
1993	

From this closing corner, the south-east standard township corner of T. 1 N., R. 4 W., monumented with an aluminum post, 2 1/2 inches diameter, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the concurrent resurvey of T. 1 N., R. 4 W., bears S. 0° 07.8' E., 6.04 chains distance.

From this same closing corner, the 1/4 section corner of section 36 only, T. 1 N., R. 4 W., monumented with an aluminum post, 2 1/2 inches diameter, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the concurrent resurvey of T. 1 N., R. 4 W., bears N. 0° 07.8' W., 33.578 chains distance.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 1 S., R. 3 W., Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by
G.C. Swan and F.C. Ferron in 1904

From the corner of sections 2, 3, 34, and 35, on the south boundary of the township, marked with a rebar, 36 inches long, 1/2 in. diameter, has been used by local surveyors and adjacent land owners as the true corner point, is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R3W	
S34	S35
S3	S2
T2S	
1993	

This corner will now function as a B.L.M. control station.

Corner is located on a west slope, 1 chain E. of hollow, which drains SE.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

N. 0° 07' E., between sections 34 and 35.

Over gentle rolling land.

40.14

The 1/4 section corner of sections 34 and 35, marked with an aluminum cap on a rebar, projecting 4 inches above ground, with aluminum cap marked: Uintah Engineering, and set alongside fence corner post, with fences projecting N, S, and W.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R3W	
1/4	
S34	S35
1993	

This point is harmoniously related to identified original corners, and is accepted as the best available evidence of the original corner position.

N. 0° 02' W., beginning new measurement.

Along N and S fence line.

38.80

Dirt road, bears S. 5° E. and N. 5° W.

39.88

The corner of sections 26, 27, 34, and 35, marked with a rebar, 1/2 in. diameter, projecting 4 inches above ground, with aluminum cap marked, "Uintah Engineering", and surrounded by a mound of stone. This point is harmoniously related to identified original corners, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R3W	
S27	S26
S34	S35
1993	

Raise a mound of stone west of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

N. 0° 02' W., between sections 26 and 27.

Over rolling land.

2.00

Bluebell Road, bears NE and SW.

40.135

Point for the 1/4 sections corner of sections 26 and 27, at proportionate distance;
there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the
ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap
marked:

T1S R3W
1/4
S27 | S26
1993

Corner is located in N and S fence line, and 50 links W. of N and S gravel road.

79.82

Point selected for the witness corner of sections 22, 23, 26, and 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the
ground, with aluminum cap marked:

WC
T1S R3W
S22 ↑ S23
S27 | S26
1993

Corner is located alongside fence corner post, with fences projecting N, S, and W,
and 2 ft. W. of power line pole.

80.27

The corner of sections 22, 23, 26, and 27, determined by a rebar set in old wooden
cattle guard in N and S fence line. This point is also in the center of right of way
fences, projecting W, and used by local surveyors and adjacent land owners as the
true corner point.

This corner point cannot be monumented.

N. 0° 07' W., between sections 22 and 23.

Over rolling land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

40.035

Point for the 1/4 section corner of sections 22 and 23, determined by fence corner, with fences projecting N, S, and W. This position is harmoniously related to existing original corners, has long been recognized as the corner point by adjacent land owners, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R3W	
1/4	
S22	S23
1993	

Raise a mound of stone west of the corner.

N. 0° 35.5' W., beginning new measurement.

0.30

Dirt road, bears E and W.

39.58

The corner of sections 14, 15, 22, and 23, monumented with a cobblestone, 12x10x8 inches, firmly set, projecting 10 inches above ground, plainly marked 3 notches on the S. and 2 notches on the E. edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R3W	
S15	S14
S22	S23
1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

Corner is located in N and S fence line, and 4 links N of fence corner.

N. 0° 06' E., between sections 14 and 15.

Over rolling land, through scattered juniper and pinon timber.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS
40.04

The 1/4 section corner of sections 14 and 15, monumented with a sandstone, 14x14x5 inches, firmly set, projecting 8 inches above ground, dimly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R3W
1/4
S15 | S14
1993

Deposit the marked stone alongside the aluminum post.

Corner is located in N and S fence line.

N. 0° 04' E., beginning new measurement.

40.12

The corner of sections 10, 11, 14, and 15, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 18 inches above ground, with aluminum cap marked: Duchesne County Survey T1S R3W S10 S11 S14 S15 1983, from which the original bearing tree:

A cedar, 10 inches diameter, bears S. 11° W., 65 links distance, with a healed over blaze.

There is no remaining evidence of the other bearing tree.

No improvements were necessary on this corner point.

N. 0° 02' E., between sections 10 and 11.

Over rolling land.

40.045

The 1/4 section corner of sections 10 and 11, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 12 inches above ground, with aluminum cap marked: Duchesne County Survey T1S R3W 1/4 S10 S11 1983. The original marked stone is buried alongside the aluminum post.

Corner is located in N and S fence line.

No improvements were necessary on this corner point.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

N. 0° 17' E., beginning new measurement.

11.00

Dirt road, bears NW. and SE.

39.995

The corner of sections 2, 3, 10, and 11, monumented with a sandstone, 12x10x3 inches, firmly set, projecting 6 inches above ground, dimly marked 5 notches on the S. and 2 notches on the E. edges, from which the original bearing tree:

A cedar, 8 inches diameter, bears S. 7° W., 1.735 chains distance,
marked T1S R3W S10 BT.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S	R3W
S3	S2
S10	S11
1993	

Deposit the marked stone alongside the aluminum post.

Corner is located in N and S fence line.

N. 0° 01' E., between sections 2 and 3.

Over gentle rolling land.

39.975

The 1/4 section corner of sections 2 and 3, monumented with a sandstone, 12x8x6 inches, firmly set, projecting 7 inches above ground, marked 1/4 on the E face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S	R3W
1/4	
S3	S2
1993	

Deposit the marked stone alongside the aluminum post.

Corner is located in N and S fence line.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

- N. 0° 14' W., beginning new measurement.
- 27.00** Dirt road, bears NW and SE.
- 46.29** Intersect the south boundary of section 35, T. 1 N., R. 3 W., on the Uintah Special Base Line, and also the closing corner of sections 2 and 3, T. 1 S., R. 3 W., hereinbefore described.
-
- From the corner of sections 10, 11, 14, and 15.
- S. 89° 50' W., between sections 10 and 15.
- Over rolling land.
- 39.745** The 1/4 section corner of sections 10 and 15, monumented with a sandstone, 7x7x2 inches, firmly set, projecting 4 inches above ground, plainly marked 1/4 on the N. face.
- At the corner point
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
- T1S R3W

1/4 S10

S15

1993
- Deposit the marked stone alongside the aluminum post.
- Raise a mound of stone north of the corner.
-
- N. 89° 54.5' W., beginning new measurement.
- 19.81** Point for the W. 1/16 section corner of sections 10 and 15.
- The corner point is not monumented.
- 39.62** Point for the corner of sections 9, 10, 15, and 16, marked with a spike in center of E-W right of way, and in line with fence projecting N. This point was established by a private surveyor, is harmoniously related to existing original corners and is accepted as the best available evidence of the original corner position, from which

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears N. 45° E., 69 links distance, with aluminum cap marked T1S R3W S10 RM 1993 45.9 ft. and an arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears N. 45° W., 71 1/2 links distance, with aluminum cap marked T1S R3W S9 RM 1993 47.1 ft. and an arrow pointing to the corner.

N. 0° 17' W., between sections 9 and 10.

Over rolling land.

0.50 Fence corner, with fences projecting E, W, and N.

20.055 Point for the S 1/16 section corner of sections 9 and 10.

The corner point is not monumented.

40.11 The 1/4 section corner of sections 9 and 10, monumented with a cobblestone, 15x10x8 inches, firmly set, projecting 10 inches above ground, plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, and in a collar of stone, with aluminum cap marked:

T1S R3W
1/4
S9 | S10
1993

Deposit the marked stone alongside the aluminum post.

N. 0° 05' W., beginning new measurement.

Ascend over SW slope.

19.995 Point for the N 1/16 section corner of sections 9 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

N 1/16
S9 | S10
1993

Raise a mound of stone west of corner.

39.99

The corner of sections 3, 4, 9, and 10, monumented with a sandstone, 10x7x5 inches, firmly set, projecting 6 inches above ground, plainly marked 3 notches on the E and 5 notches on the S edges.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R3W
S4 | S3
S9 | S10
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

From the corner of sections 2, 3, 10, and 11.

N. 89° 50' W., between sections 3 and 10.

Over rolling land.

21.00

Dirt road, bears NW and SE.

39.78

The 1/4 section corner of sections 3 and 10, monumented with a sandstone, 14x10x5 inches, firmly set, projecting 8 inches above ground, plainly marked 1/4 on the N face, from which the remaining original bearing tree

A cedar stump, 12 inches diameter, bears S. 61° 30' W.,
41 links distance.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R3W
1/4 S3
S10
1993

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

S. 89° 50.5' W., beginning new measurement.

20.02 Point for the W 1/16 section corner of sections 3 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

W 1/16 S3
 S10
 1993

Raise a mound of stone north of the corner.

40.04 The corner of sections 3, 4, 9, and 10.

N. 0° 01' W., between sections 3 and 4.

Over rolling land.

20.01 Point for the S 1/16 section corner of sections 3 and 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

S 1/16
S4 | S3
1993

Set a steel fence post alongside the aluminum post.

40.02 The 1/4 section corner of sections 3 and 4, monumented with a sandstone, 20x10x5 inches, firmly set, projecting 10 inches above ground, plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

T1S R3W
1/4
S4 | S3
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

N. 0° 36' E., beginning new measurement.

45.91

Intersect the south boundary of section 34 on the Uintah Special Base Line, T. 1 N., R. 3 W., and also the closing corner of sections 3 and 4, T. 1 S., R. 3 W., hereinbefore described.

The point for the N. 1/4 section corner of section 3, T. 1 S., R. 3 W., is at mid-point on the north boundary of section 3.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1N
1/4 S 3
T1S R3W
1993

Raise a mound of stone south of the corner.

From this point the standard 1/4 section corner of section 34, T. 1 N., R. 3 W., bears S. 89° 12' W., 9.00 chains dist.

From the corner of sections 3, 4, 9, and 10.

West, between sections 4 and 9.

Over rolling land.

20.21

Point for the E 1/16 section corner of sections 4 and 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, and in a collar of stone, with aluminum cap marked:

E 1/16 S4
S9
1993

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS
40.42

The 1/4 section corner of sections 4 and 9, monumented with a sandstone, 12x10x6 inches, firmly set, projecting 8 inches above ground, dimly marked 1/4 on the N. face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R3W
1/4 S4
 S9
 1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone north of the corner.

Corner is located 2 links E. and 2 links N. of old fence corner post.

From the corner of sections 4, 5, 8, and 9, marked by a galvanized post, 2 1/2 inches diameter, firmly set, projecting 10 inches above mound of stone, with a galvanized cap marked T1S R3W S4 S5 S8 S9 1960. The original stone is buried alongside the galvanized post.

No improvements were made on this corner.

N. 0° 06.5' W., between sections 4 and 5.

Over rolling and broken land.

19.835 Point for the S 1/16 section corner of sections 4 and 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

S 1/16
S5 | S4
1993

Raise a mound of stone west of the corner.

39.67 The 1/4 section corner of sections 4 and 5, monumented with a sandstone, 16x12x8 inches, firmly set, projecting 6 inches above ground, plainly marked 1/4 on the W face.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R3W
1/4
S5 | S4
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

N. 0° 08.5' E., beginning new measurement.

24.00 Trail road, in bottom of Jeep Hollow, bears NW and SE.

46.125 Intersect the south boundary of section 33, T. 1 N., R. 3 W., on the Uintah Special Base Line, and also the closing corner of sections 4 and 5, T. 1 S., R. 3 W., hereinbefore described.

The point for the N 1/4 section corner of section 4 only, T. 1 S., R. 3 W., on the Uintah Special Base Line, is at midpoint on the north boundary of section 4.

Set an aluminum post, 30 inches long, 2 1/2 diameter, 24 inches in the ground, with aluminum cap marked:

T1N
1/4 S4
T1S R3W
1993

Raise a mound of stone south of the corner.

From this point the standard 1/4 section corner of section 33, T. 1 N., R. 3 W., bears S. 89° 49' W., 9.25 chains distance, heretofore described.

From the corner of sections 4, 5, 8, and 9.

S. 89° 49.5' W., between sections 5 and 8.

Over rolling and broken land.

19.96 Point for the E 1/16 section corner of sections 5 and 8.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15 inches in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

E 1/16 S5
 S8
 1993

39.92

The 1/4 section corner of sections 5 and 8, monumented with a cobblestone, 18x16x10 inches, firmly set, projecting 10 inches above ground, plainly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T1S R3W
1/4 S5
 S8
 1993

Deposit the marked stone alongside the aluminum post.

S. 89° 35.5' W., beginning new measurement.

39.955

The corner of sections 5, 6, 7, and 8, determined from the remaining bearing tree

A pinon, 14 inches diameter, bears N. 55° E., 57 links distance,
marked T1S R3W S5 BT.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R3W
S6 | S5
S7 | S8
1993

Raise a mound of stone west of the corner.

N. 0° 16' E., between sections 5 and 6.

Over rolling and broken land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINE, T. 1 N., R. 3 W., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

39.48

The 1/4 section corner of sections 5 and 6, monumented with a cobblestone, 20x10x6 inches, firmly set, projecting 8 inches above ground, plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

T1S R3W
1/4
S6 | S5
1993

Deposit the marked stone alongside the aluminum post.

The point for the N. 1/4 section corner of section 5 only, T. 1 S., R. 3 W., on the Uintah Special Base Line, is at midpoint on the north boundary of section 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

T1N
1/4 S5
T1S R3W
1993

From this point the standard 1/4 section corner of section 32, T. 1 N., R. 3 W., on the Uintah Special Base Line, bears S.89 45' W., 9.06 chains dist.

The Subdivision of Section 3,
T. 1 S., R. 3 W., Uintah Special Meridian, Utah

From the 1/4 section corner of sections 3 and 10.

North, along the N-S center line of section 3.

Over rolling and broken land.

39.89

Point for the center 1/4 section corner, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 3,
T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

T1S R3W
C 1/4 S3
1993

Raise a mound of stone west of the corner.

50.00

Dirt road, bears NW and SE.

85.72

The 1/4 section corner of section 3 only, T. 1 S., R. 3 W., hereinbefore described.

From the 1/4 section corner of sections 2 and 3.

N. 89° 57.5' W., on the E-W center line of section 3.

Over rolling and broken land.

35.00

Dirt road, bears NW and SE.

39.775

The center 1/4 section corner of section 3.

59.81

Point for the center W 1/16 section corner of section 3.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, and in a collar of stone, with aluminum cap marked:

C $\frac{W \ 1/16}{S3}$ C
1993

Raise a mound of stone north of the corner.

79.845

The 1/4 section corner of sections 3 and 4.

From the W 1/16 section corner of sections 3 and 10.

N. 0° 00.5' W., on the N-S center line of the SW 1/4 of section 3.

Over rolling and broken land.

39.955

The center W 1/16 section corner of section 3.

The Subdivision of Section 4,
T. 1 S., R. 3 W., Uintah Special Meridian, Utah

THE SUBDIVISION OF SECTION 4,
T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 4 and 9.

N. 0° 19.5' E., on the N-S center line of section 4.

Over rolling land.

19.935 Point for the center S 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, and in a collar of stone, with aluminum cap marked:

C
S 1/16 | S4
C
1993

39.87 Point for the center 1/4 section corner, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top, with aluminum cap marked:

T1S R3W
C 1/4 S4
1993

85.905 The 1/4 section corner of section 4 only, T. 1 S., R. 3 W., on the Uintah Special Base Line, hereinbefore described.

From the 1/4 section corner of sections 3 and 4.

S. 89° 47' W., on the E-W center line of section 4.

Over rolling and broken land.

20.085 Point for the center E. 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C — E 1/16 — C
S4
1993

Raise a mound of stone north of the corner.

32.00 Dirt road, bears NE and SW.

THE SUBDIVISION OF SECTION 4,
T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

40.17

The center 1/4 section corner of section 4.

80.405

The 1/4 section corner of sections 4 and 5.

From the E. 1/16 section corner of sections 4 and 9.

N. 0° 09' E., on the N-S center line of the SE 1/4 of section 4.

Over rolling and broken land.

19.975

Point for the SE 1/16 section corner of section 4, at intersection with the E-W center line of the SE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

SE 1/16
S4
1993

39.95

The center E. 1/16 section corner of section 4.

From the S. 1/16 section corner of sections 3 and 4.

S. 89° 53.5' W., on the E-W center line of the SE 1/4 of section 4.

Over rolling and broken land.

20.145

The SE 1/16 section corner of section 4.

40.29

The center S 1/16 section corner of section 4.

S. 89° 55.5' W., on the E-W center line of the SW 1/4 of section 4.

Over rolling land.

40.08

The S 1/16 section corner of sections 4 and 5.

The Subdivision of Section 5,
T. 1 S., R. 3 W., Uintah Special Meridian, Utah

THE SUBDIVISION OF SECTION 5,
T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 5 and 8.

N. 0° 04' E., on the N-S center line of section 5.

19.75

Point for the center S 1/16 section corner of section 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{C} \\ \text{S } 1/16 \quad | \quad \text{S5} \\ \text{C} \\ 1993 \end{array}$$

Raise a mound of stone west of corner.

39.50

Point for the center 1/4 section corner, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T1S R3W} \\ \text{C } 1/4 \text{ S5} \\ 1993 \end{array}$$

Raise a mound of stone west of the corner.

85.77

The 1/4 section corner of section 5 only, T. 1 S., R. 3 W., on the Uintah Special Base Line, hereinbefore described.

From the 1/4 section corner of sections 4 and 5.

S. 89° 35' W., on the E-W center line of section 5.

Over rolling and broken land.

19.89

Point for the center E 1/16 section corner of section 5.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

$$\begin{array}{c} \text{C} \quad \frac{\text{E } 1/16}{\text{S5}} \quad \text{C} \\ 1993 \end{array}$$
39.78

The center 1/4 section corner of section 5.

THE SUBDIVISION OF SECTION 9,
T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS
79.61

The 1/4 section corner of sections 5 and 6.

From the E. 1/16 section corner of sections 5 and 8.

N. 0° 01.5' W., on the N-S center line of the SE 1/4 of section 5.

Over rolling and broken land.

19.79

Point for the SE 1/16 section corner of section 5, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

SE 1/16 S5
1993

Raise a mound of stone west of the corner.

39.58

The center E 1/16 section corner of section 5.

From the S 1/16 section corner of sections 4 and 5.

S. 89° 42.5' W., on the E-W center line of the SE 1/4 of section 5.

Over rolling and broken land.

19.925

The SE 1/16 section corner of section 5.

39.85

The center S 1/16 section corner of section 5.

The Subdivision of Section 9,
T. 1 S., R. 3 W., Uintah Special Meridian, Utah

From the 1/4 section corner of sections 9 and 16, marked with a spike in the center of E and W dirt road and right-of-way, and in line with fence extending N. This point is harmoniously related to existing original corners and is accepted as the best available evidence of the original corner position, from which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears N. 45° E., 0.632 chains distance, with aluminum cap marked T1S R3W 1/4 S9 RM 1993 41.7 ft. Reference monument is located in an E and W fence line.

THE SUBDIVISION OF SECTION 9,
T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS	
	<p>An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears N. 45° W., 0.683 chains distance, with aluminum cap marked T1S R3W 1/4 S9 RM 1993 45.1 ft. Reference monument is located in an E and W fence line.</p> <p>N. 0° 12' W., on the N-S center line of section 9.</p> <p>Over rolling land.</p>
0.465	Fence corner, with fences extending E, W, and N.
40.02	<p>Point for the center 1/4 section corner of section 9, at intersection with the E-W center line.</p> <p>This point falls in cultivated land and is not monumented.</p>
60.04	<p>Point for the center N 1/16 section corner of section 9.</p> <p>Corner point not monumented.</p>
80.06	<p>The 1/4 section corner of sections 4 and 9.</p> <hr/> <p>From the 1/4 section corner of sections 9 and 10.</p> <p>S. 89° 55' W., on the E-W center line of section 9.</p> <p>Over rolling land.</p>
20.165	<p>Point for the center E 1/16 section corner of section 9.</p> <p>Corner point not monumented.</p>
40.33	The center 1/4 section corner of section 9.
80.26	<p>The 1/4 section corner of sections 8 and 9, monumented with a cobblestone, 15x6x6 inches, firmly set, projecting 5 inches above ground, plainly marked 1/4 on the W face.</p> <p>No improvements were made on this corner point.</p> <p>Corner is located by fence corner post, with fences extending N, S, and E.</p> <hr/>

THE SUBDIVISION OF SECTION 9,
T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

- From the point for the center E 1/16 section corner of section 9.
- N. 0° 09' W., on the N-S center line of the NE 1/4 of section 9.
- Over rolling land.
- 20.01** Point for the NE 1/16 section corner of section 9, at intersection with the E-W center line of the NE 1/4.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:
- NE 1/16 S9
1993
- Raise a mound of stone west of the corner.
- 40.02** The E 1/16 section corner of sections 4 and 9.
-
- From the N. 1/16 section corner of sections 9 and 10.
- S. 89° 57.5' W., on the E-W center line of the NE 1/4 of section 9.
- Over rolling land.
- 20.19** The NE 1/16 section corner of section 9.
- 40.38** Point for the center N 1/16 section corner of section 9.
-
- The Subdivision of Section 10,
T. 1 S., R. 3 W., Uintah Special Meridian, Utah
-
- From the 1/4 section corner of sections 10 and 15.
- N. 0° 08' E., on the N-S center line of section 10.
- Over rolling land.
- 20.085** Point for the center S 1/16 section corner of section 10.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 10,
T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

C
S 1/16 | S10
C
1993

40.17 Point for the center 1/4 section corner, at intersection with the E-W center line.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R3W
C 1/4 S10
1993

Raise a mound of stone west of corner.

60.22 Point for the center N 1/16 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C
N 1/16 | S10
C
1993

Raise a mound of stone west of corner.

80.27 The 1/4 section corner of sections 3 and 10.

From the 1/4 section corner of sections 10 and 11.

N. 89° 59' W., on the E-W center line of section 10.

Over rolling land.

39.67 The center 1/4 section corner of section 10.

59.63 Point for the center W 1/16 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C — W 1/16 — C
S10
1993

Raise a mound of stone north of the corner.

THE SUBDIVISION OF SECTION 10,
T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS
79.59

The 1/4 section corner of sections 9 and 10.

From a point for the W. 1/16 section corner of sections 10 and 15.

N. 0° 05' W., on the N-S center line of the SW 1/4 of section 10.

Over rolling land.

20.07

Point for the SW 1/16 section corner of section 10, at intersection with the E-W center line of the SW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

SW 1/16 S10
1993

Corner is located 10 ft. N. and 10 ft. W of fence corner.

40.14

The center W 1/16 section corner of section 10.

From the center S. 1/16 section corner of section 10.

N. 89° 57' W., on the E-W center line of the SW 1/4 of section 10.

19.885

The SW 1/16 section corner of section 10.

39.77

Point for the S 1/16 section corner of sections 9 and 10.

From the center W. 1/16 section corner of section 10.

N. 0° 01.5' E., on the N-S center line of the NW 1/4 of section 10.

Over rolling land.

20.025

Point for the NW 1/16 section corner of section 10, at intersection with the E-W center line of the NW 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

NW 1/16 S10
1993

Raise a mound of stone west of the corner.

THE SUBDIVISION OF SECTION 10,
T. 1 N., R. 3 W., UTAH SPECIAL MERIDIAN, UTAH

CHAINS
40.05

The W 1/16 section corner of sections 3 and 10.

From the center N 1/16 section corner of section 10.

S. 89° 55.5' W., on the E-W center line of the NW 1/4 of section 10.

Over rolling land.

19.99

The NW 1/16 section corner of section 10.

39.98

The N 1/16 section corner of sections 9 and 10.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Frank C. Profaizer	Cadastral Surveyor
Brandon Sanchez	Survey Technician
Casey Toomer	Survey Technician


CERTIFICATE OF SURVEY

I, **Jerry L. Thomas, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **24th day of March 1993**, I have *dependently resurveyed a portion of the north boundary (Uintah Special Base Line), a portion of the subdivisional lines and subdivided sections 3, 4, 5, 9, and 10, in Township 1 South, Range 3 West,*

of the **Uintah Special Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 12, 1999

Date


(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah


The foregoing field notes of the *dependent resurvey of a portion of the north boundary (Uintah Special Base Line), a portion of the subdivisional lines and the subdivision of sections 3, 4, 5, 9, and 10, Township 1 South, Range 3 West, Uintah Special Meridian, Utah,*

executed by **Jerry L. Thomas, Cadastral Surveyor**

having been critically examined and found correct, are hereby approved.

May 18, 1999

Date


(Chief Cadastral Surveyor for Utah)